#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization International Bureau



### 

## (43) International Publication Date 6 May 2004 (06.05.2004)

#### **PCT**

# (10) International Publication Number WO 2004/038279 A2

(51) International Patent Classification7:

**F17C** 

(21) International Application Number:

PCT/US2003/034140

(22) International Filing Date: 23 October 2003 (23.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/420,543

23 October 2002 (23.10.2002) US

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:

US

Not furnished (CON)

Filed on

Not furnished (CON)

Not furnished


- (71) Applicant (for all designated States except US): SAUDI ARABIAN OIL COMPANY [SA/SA]; R-3296, Administration Building, Dhahran 31311, SA (SA).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): AL-KHALIFA,

Hani [SA/SA]; c/o Saudi Aramco, P.O. Box 1380, #2540, Udhailiyah, SA (SA). DELEVAN, Donald, P. [US/US]; 3125 Birnamwood Dr., Colorado Spring, CO 80920 (US). WILSON, Timothy, T. [US/US]; 1308 Mark Street, George West, TX 78022 (US). AL-ABDULLATIF, Abdulrahman [SA/SA]; 2216 Al Khobar Ave, UDH (SA).

- (74) Agent: SPATH, Thomas, E.; Abelman, Frayne & Schwab, 150 East 42nd Street, New York, NY 10017-5612 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: CONTROLLED SUPERHEATING OF NATURAL GAS FOR TRANSMISSION



(57) Abstract: A method is provided for controlling superheating and temperature of a compressed natural gas stream and the addition of a corrision inhibitor composition for transmission through a pipeline that includes: a. dividing a stream of natural gas discharged from a high pressure gas compressor (106) into a first portion (108) and a second portion (202); b. passing the first portion (108) of the gas from the gas compressor to a heat exchanger (112) to heat the gas to a predetermined temperature; c. passing the first portion of gas (111) exiting the heat exchanger to an aftercooler (114); d. passing the second portion (202) of natural gas discharged from the gas compressor (106) to the aftercooler (114) without passing it through the heat exchanger (112), the second portion of gas and the first portion of gas being mixed at the

aftercooler inlet and cooled by the aftercooler and discharged from the aftercooler as a cooled gas stream (116) having a temperature no greater than a first temperature; e. passing the cooled gas stream (116) from the aftercooler to a liquid discharge drum (118) to remove condensate from the cooled gas and discharging from the drum a partially dried gas stream (120) at a second temperature; f. passing the partially dried gas stream (120) from the discharge drum to the heat exchanger (112) in heat exchanging relation with the first portion of gas (108) from the gas compressor, and superheating at least a portion of the gas stream (120) to a third temperature to provide a superheated gas stream (129), the third temperature being controlled by an automated control loop responsive to a differential pressure across the gas compressor (106); and g. passing the superheated gas stream (129) into a transmission tie-line (256) and injecting a predetermined amount of a corrosion inhibitor composition into the tie-line to mix with the superheated gas stream, where the amount of corrosion inhibitor injected is proportioned in response to the third temperature.

### WO 2004/038279 A2



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

#### Published:

 without international search report and to be republished upon receipt of that report